


LED
Recessed
Round-Light
 200mm
Commercial
Architectural
Residential



Oxtron is pleased to introduce the first product in this new series of LED based, energy saving, high efficiency, Commercial, Architectural, and Residential 6" (200mm) Recessed Round Down-light.

The LED Recessed Round 6" (200mm) Down-light incorporates the very latest high lumen per watt WLED (White LEDs) into a stylish low profile die-cast aluminium housing with an optical grade acrylic treated acrylic aperture.

The LED Recessed Round 6" (200mm) Down-light is designed as a direct to AC, energy savings replacement to high energy traditional lamp based versions. The LED Recessed Round 6" (200mm) Down-light incorporates a linear dimmable AC to DC Constant Current Driver to enable direct replacements in environments where dimming is desired or already supplied.

Whether for new construction or retrofit the LED Recessed Round 6" (200mm) Down-light from Oxtron is the ideal solution. The LED Recessed Round 6" (200mm) Down-light is also available in a variety of colour temperatures to suit your individual application and venue.

Available Kelvin Temperature

CCT Name	Code	Correlated Kelvin	Binning Variation
Pure White	B0101-PW	5500K	+/- 500K
Cool White	B0101-CW	7500K	+/- 500K
Warm White	B0101-WW	3000K	+/- 500K



Technical Specification

Item Number	Diameter	Power consumption	Beam Angle	Input Voltage	Operating Current	Material
B0101-PW/CW/WW	200mm	10 x 1W	59°	120VAC/220VAC	350mA	Die-cast Aluminium